

# MATERIAL SAFETY DATA SHEET

ACECROFT PTY LTD  
Unit 21, Axxess Corporate Park  
170 Forster Road  
PO Box 900  
MT WAVERLEY VIC 3149

INCA™ TIMBERWAX LIQUID

Page 1 of 3  
Date of Issue: December 1998  
ABN:14 007 220 519

Telephone (03) 9544 0174

No Emergency

Fax No. (03) 9543 4156

Please contact Poisons Information on  
**13 11 26**

Date of Issue: 1st December 1998

## IDENTIFICATION

Product Name: **INCA TIMBERWAX LIQUID**  
Other Names: Timber furniture wax  
Product Code: None

UN Number: Not Required  
Dangerous Goods Class and Sub-risk: Not Required  
Hazchem Code: Not Required  
Poisons Schedule: Not Required  
Packaging Group: Not Required  
Emergency Procedure Guide: Not Required

**Use:** Manually applied to timber furniture as a protective coating.

### **Physical Description/Properties:**

Appearance: Pale yellow, opaque, gel with eucalyptus oil and honey wax.  
Boiling Point: approx 210°C  
Vapour Pressure: 0.5kPa mm Hg at 38°C  
Specific Gravity: 0.75  
Flashpoint (°C): 65°C  
Flammability Limits (%): Lel 0.6 Uel 7.0

### **Other Properties:**

Solubility: Not soluble in water  
Melting Point: Approx 65°C  
Vapour Density: 5.9 (Air = 1)

### **Ingredients:**

| <b>Chemical Entity</b> | <b>CAS No:</b> | <b>Proportion</b> |
|------------------------|----------------|-------------------|
| Beeswax                | N/A            | 10 to 30%         |
| Paraffin Wax           | 8002-74-2      | 10 to 30%         |
| Petroleum hydrocarbons | 64771-72-8     | 40 to 70%         |
| Eucalyptus Oil         | 8000-48-4      | 1 to 2%           |
| Linseed Oils           | 68649-95-6     | 3 to 15%          |
| Dyes oil brown         | 2653-64-7      |                   |
| oil black              | 4197-25-5      | 1 to 3%           |

# MATERIAL SAFETY DATA SHEET

INCA™ TIMBERWAX LIQUID

Page 2 of 3

Date of Issue: December 1998

## HEALTH HAZARD INFORMATION

### Health Effects

|                              |            |   |
|------------------------------|------------|---|
| <b>Acute:</b>                | Swallowed: | May cause irritation to the mouth, throat and stomach.  |
|                              | Eye:       | Harmful to the eyes. Eye irritant.  |
|                              | Skin:      | Contact with the skin may result in irritation. Prolonged or repeated contact with skin may lead to dermatitis effects.                                 |
|                              | Inhaled:   | Low toxicity and not a normal feature of this product.  |
| <b>Chronic:</b>              |            | None known.   |
| <b>First Aid:</b>            | Swallowed: | Remove material from mouth. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water (or milk). Do not induce vomiting. Seek medical attention. |
|                              | Eye:       | Hold eyelids open and flush eyes with water for at least 15 minutes. Seek medical attention.  |
|                              | Skin:      | Wash skin thoroughly with water. Remove contaminated clothing. Seek medical attention if any irritations occur.   |
|                              | Inhaled:   | Remove to fresh air. Keep warm and seek medical advice.   |
| <b>First Aid Facilities:</b> |            | Emergency eyewash station and shower.   |
| <b>Advice to Doctor:</b>     |            | Treat Symptomatically.  |

## PRECAUTIONS FOR USE

|                              |  |
|------------------------------|--|
| <b>Exposure Standards:</b>   | Exposure standard –TLV, No exposure limits set by National Health and Medical Research. Up to 300 pm Recommended per 8hr/day/5 days. |
| <b>Engineering Controls:</b> | use in ventilated areas.   |
| <b>Personal Protection:</b>  | Avoid contact with eyes and skin. Wash hands after use.  |
|                              | Clothing: Overalls recommended.  |
|                              | Goggles: Eye protection recommended.   |
|                              | Gloves: Solvent resistant gloves recommended   |

All safety equipment should comply with Australian Standards or an equivalent, approved by a State or Territory Authority.

**Flammability:** Combustible, vapors may create flammable/explosive atmosphere on heating above flash point.

# MATERIAL SAFETY DATA SHEET

INCA™ TIMBERWAX LIQUID

Page 3 of 3

Date of Issue: December 1998

## SAFE HANDLING INFORMATION

***Storage & Transport:***

Keep containers securely sealed and protected against damage. Non regulated goods. Store in a cool place and away from naked flames and heat.

***Spills & Disposal:***

Eliminate sources of ignition, shovel up and place in an approved container for disposal. Use absorbent material if required. Consult local authority on disposal

**Note: Precautions to be observed by clean up crew – protective clothing must be worn. Care should be taken not to slip on contaminated area.**

***Fire/Explosion Hazard:***

Use foam, dry chemical, Carbon Dioxide or water fog. Keep product out of sewer and watercourses.

***Other information:***

Do not store near strong oxidizing agents.

## OTHER INFORMATION:

Before being marketed, Acecroat Pty Ltd products are carefully screened for potential hazards to the user, and where necessary a warning or advice for use in on the label. However, as with all chemicals if improperly used, the products can be harmful, hence guidelines and recommendations to first aid treatment are provided.

## CONTACT POINT:

Technical Manager (business hours) (03) 9544 0174  
ACECROFT PTY LTD  
OR THE POISONS INFORMATION CENTRE 24 hours 13 11 26

**THE DATA CONTAINED HEREIN IS NOT TO BE TAKEN AS A WARRANTY OR REPRESENTATION FOR WHICH ACECROFT PTY LTD ASSUMES LEGAL RESPONSIBILITY. THEY ARE OFFERED SOLELY FOR YOUR CONSIDERATION AND VERIFICATION.**

**Date Reveiwed:** 1<sup>st</sup> December 1998 **Authorised By:**.....