

# Material Safety Data Sheet

Acecroft Pty Ltd  
Unit 13 Axxess Corporate Park  
170 Forster Rd  
P O Box 900  
Mt Waverley Vic 3149

## OUTDOOR FURNITURE PROTECTOR

Page 1 of 3  
Date of Issue: February 2001  
ABN 14 007 220 519

Telephone (03) 9544 0144  
Fax No (03) 9543 4156

No Emergency Number  
Please contact Poisons Information Centre on 13 1126

### STATEMENT OF HAZARDOUS NATURE

Hazardous according to criteria of "Worksafe Australia"

### IDENTIFICATION OF PRODUCT PARAMETERS

Product Name: Outdoor Furniture Protector  
Poison Schedule: Number S5  
Use: Timber Coating  
Dangerous Goods Class and Subsidiary Risk: Nil

### PHYSICAL PROPERTIES - DESCRIPTION

Appearance: Amber Liquid  
Boiling Point: 180 deg C to 220 deg C  
Vapour Pressure: 20 deg C: 0.1kPa  
Flammability Limits: >200 deg C  
Solubility in Water: <0.10w/w  
Non volatile: contents: 65%  
Viscosity: 25 deg C mPas 1700 - 2300  
Acid value: mg KOH/g5 -10  
Density @ 20 deg C 0.790  
Type of fatty acid: Linoleic/Sesquiterpene  
Aics Status: Listed Cas Number 64742-48-9

### INGREDIENTS

Cypress Oil  
Eremophila Oil  
Linoleic Resin  
White Spirit  
Petroleum Hydrocarbons

# Material Safety Data Sheet

## HEALTH HAZARDS

### SWALLOWED:

The liquid is discomforting and may be harmful if swallowed.  
Ingestion may result in nausea, pain and vomiting.  
Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.  
Considered an unlikely route of entry in commercial industry application.

### EYE:

Will cause discomfort.

### SKIN:

Low order of toxicity.

### CHRONIC:

Skin: Frequent contact may cause defatting leading to dermatitis.  
Inhaled Exposure to high concentrations of vapour may be irritating to eyes and lungs may cause dizziness  
And headaches; may have other central nervous system effects including anaesthesia.

## FIRST AID

**Swallowed:** Do not induce vomiting, Keep at rest, Get prompt medical attention.  
**Eyes:** Flush eyes with large amounts of water, if irritation persists, get medical attention.  
**Skin:** Flush with large amounts of water, remove and dispose of contaminated clothing and footwear.  
**Inhaled:** remove affected victim from exposure, administer artificial respiration if breathing has stopped.  
Keep at rest, call for medical attention.  
First Aid Facilities.

## ADVICE TO DOCTOR

Treat symptomatically.

## PRECAUTIONS FOR USE

**Exposure standards:** 300ppm

**Engineering Controls:** Proper ventilation to ensure no build up of fumes.

**Personal Protection:** Use of safety glasses and chemical resistant gloves is recommended.

**Flammability:** Low Hazard. Can form flammable mixture or can burn only upon heating to temperatures at or above flashpoint. Can accumulate static charges which can cause an incendiary electric discharge.