

MATERIAL SAFETY DATA SHEET

ACECROFT PTY LTD
Unit 21, Axxess Corporate Park
170 Forster Road
PO Box 900
MT WAVERLEY VIC 3149

SCRATCH FIX PENS

Page 1 of 2
Date of Issue: November 2002
ABN: 007 220 519

Telephone (03) 9544 0174

Fax No. (03) 9543 4156

Please contact Poisons Information on
13 11 26

PRODUCT NAME AND REFERENCE NO.

Scratch Fix Pen
SFP plus colour code (5 colours)

COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT: Xylene

This product is not considered to be a hazardous substance as defined under OSHA's Hazard Communication Standard (29 CFR 1910,1200).

STATEMENT OF HAZARDOUS NATURE

CAUTION: Product vapours are flammable.
Packaging may be subject to ignition by fire and may release toxic or other irritating gases.

FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with large amounts of water for at least 15 minutes. Seek medical attention.
SKIN CONTACT: Wash skin with soap and water. Seek medical attention in the unlikely event that irritation occurs.
INGESTION: Seek medical assistance.
INHALATION: If symptomatic, move to fresh air and seek medical attention.

HANDLING & STORAGE:

HANDLING: Contents will stain. The use of smocks and gloves to protect personal clothing is suggested. Wash hands and surface after use.
STORAGE: Do not store near heat or open flame. Product vapours are flammable.

MATERIAL SAFETY DATA SHEET

ACECROFT PTY LTD
Unit 21, Axxess Corporate Park
170 Forster Road
PO Box 900
MT WAVERLEY VIC 3149

SCRATCH FIX PENS

Page 2 of 2
Date of Issue: November 2002
ABN: 007 220 519

Telephone (03) 9544 0174

Fax No. (03) 9543 4156

Please contact Poisons Information on
13 11 26

EXPOSURE CONTROL / PERSONAL PROTECTION

VENTILATION: The use of local ventilation is recommended
EYE PROTECTION: Eye protection is recommended.
SKIN PROTECTION: No special skin protection required. Wash skin if irritation is experienced.

PHYSICAL DATA

APPEARANCE: Ink filled metal barreled fibre tip marker.
COLOUR: Assorted colours in the range.
ODOR: Slight lemon type solvent
PH: NA
SPECIFIC GRAVITY: 0.91
BOILING POINT: 139 deg C
MELTING POINT: Not Established
SOLUBILITY: Not Established
EVAPORATION RATE: 0.8
VAPOUR DENSITY: 5
POUR POINT C (F) Not Established
FREEZING POINT C (F): Not Established

STABILITY AND REACTIVITY

GENERAL: This product is stable and hazardous polymerization will not occur.
INCOMPATIBILITY: None known
HAZARDOUS DECOMPOSITION: As with all burning organic matter, carbon monoxide and other toxic fumes may be released.

MATERIAL SAFETY DATA SHEET

ACECROFT PTY LTD
Unit 21, Axxess Corporate Park
170 Forster Road
PO Box 900
MT WAVERLEY VIC 3149

PUTTY BRICKS

Page 3 of 3
Date of Issue: November 2002
ABN: 007 220 519

Telephone (03) 9544 0174

Fax No. (03) 9543 4156

Please contact Poisons Information on
13 11 26

FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon Dioxide, dry chemical or foam Recommended. Apply water to cool exposed Closed containers.

SPECIAL FIRE FIGHTING PROCEDURES: Self contained breathing apparatus and full protective equipment recommended.

UNUSUAL FIRE & EXPLOSION HAZARDS: Packaging may be subject to ignition by fire and may release toxic gases.

ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Sweep or wipe up material. Place spilled material into appropriate waste containers for disposal.

LARGE SPILL: Sweep or wipe up material. Place spilled material into appropriate waste containers for disposal.

DISPOSAL CONSIDERATIONS:

Contain and place in approved container. Dispose of per Local, State and Federal regulations.

All safety equipment should comply with Australian Standards or an equivalent approved by a State or Territory Authority.

THE DATA CONTAINED HEREIN IS NOT TO BE TAKEN AS A WARRANTY OR REPRESENTATION FOR WHICH ACECROFT PTY LTD ASSUMES LEGAL RESPONSIBILITY. THEY ARE OFFERED SOLELY FOR YOUR CONSIDERATION AND VERIFICATION.